



# MOD-U-VENT ATHLETIC LOCKERS



**STRONG**

**SILENT  
NO MOVING PARTS**

**SECURE**

**MAINTENANCE FREE**

**16 GAUGE  
CONTINUOUS  
ONE-PIECE HINGE  
& FRAME**

STANDARD FINISH: HIGH PERFORMANCE POLYMER COATING  
AVAILABLE IN ULTRA ABRASIVE AND GRAFFITI RESISTANT COATING

## Standard Sizes Available

	12" WIDE	15" WIDE	18" WIDE	24" WIDE
<b>72" HIGH</b>				
Single Tier	12", 15", 18", 21" Deep	15", 18", 21" Deep	18", 21", 24" Deep	18", 21", 24" Deep
Double Tier	12", 15", 18", 21" Deep	15", 18", 21" Deep	18", 21", 24" Deep	18", 21", 24" Deep
Triple Tier	12", 15", 18", 21" Deep	15", 18", 21" Deep	18", 21", 24" Deep	
Four Tier	Contact Factory	Contact Factory	Contact Factory	
Six Tier	12", 15", 18", 21" Deep	15", 18", 21" Deep	18", 21", 24" Deep	
<b>60" HIGH</b>				
Single Tier	12", 15", 18", 21" Deep	15", 18", 21" Deep	18", 21", 24" Deep	18", 21", 24" Deep
Double Tier	12", 15", 18", 21" Deep	15", 18", 21" Deep	18", 21", 24" Deep	18", 21", 24" Deep
Triple Tier	Contact Factory	Contact Factory	Contact Factory	
Five Tier	12", 15", 18", 21" Deep			
<b>48" HIGH</b>				
Single Tier	12", 15", 18", 21" Deep	15", 18", 21" Deep	18", 21", 24" Deep	
Double Tier	Contact Factory	Contact Factory	Contact Factory	

NOTE: For minimum quantities and other sizes, contact the Factory

### Mod-U-Vent Specifications:

**Outer doors** are made with a 16 gauge (14 gauge for the Mod-U-Vent II) outer door panel formed with channels on both sides, top and bottom.

**Inner door** is a full size 22 gauge panel which conceals the back of the pocket to eliminate vandalism. It is formed with channels on both sides, interlocked with the outer panel and mig-welded to the outer door at the top, bottom and sides to create a box welded door 1-1/8" thick.

**Inner and outer doors** have a staggered 3/8" x 1" perforations to provide the ultimate combination of ventilation and privacy.

**Door closes** on a 16 gauge frame member with a 5/8" wide closure strike the full height of the door, and fits flush with the outside of the frame.

**Doors are hung** on 16 gauge **continuous one-piece** right hand **hinge and frame**.

### Bodies:

**Locker sides, backs, tops, bottoms and shelves** are fabricated from 16 gauge cold rolled steel.

**Sides** provide ventilation to adjacent lockers through 3/4" x 1-1/4" diamond shaped perforations.

**Backs** have right angle flanges on the vertical sides.

**Tops, bottoms and shelves** are flanged on all sides and free of sharp edges.

**Edges are suitably formed** to provide a **rigid** bolted or riveted assembly.

### Single Point Latching:

**Stainless steel recessed pocket** provides durability and maintenance free operation.

**One piece 12 gauge hasp** is channel formed and welded on both legs of the 16 gauge frame member.

**Quiet operation** is achieved with two rubber grommets, and a nylon friction catch which cushions the door.

### Distributed By

### Material:

**Cold Rolled Steel free from surface imperfections** is used for all components.

**Galvaneal Steel** is available for areas with high humidity.

### Finish:

**Powder Coat** painting of all components provides a durable scratch resistant finish. Sides, backs, tops, bottoms and shelves are finished in reflecting 223 Oyster Grey.

NOW AVAILABLE: **ULTRA ABRASION AND GRAFFITI RESISTANT POLYMER POWDER COATING** providing a tough and durable 4H (ASTM D3363 rating) surface finish and when cleaned with **GRAFFITI FREE** cleaner, can remove 95% of all marker and other ink stains from the surface without sacrificing the finish.

### Note:

**Five Tier** and **Six Tier Lockerettes** have a single pan door.

**Installation:** Lockers shall be securely fastened to the wall and/or floor at least every third locker.

**Policy:** In keeping with our policy of constant improvement, all designs and specifications are subject to change without notice.

**Care:** The **Mod-U-Vent** Locker provides a very durable attractive finish with a long life expectancy, however, high humidity alone or in conjunction with chlorine, salts, acids, strong disinfectants or abrasive cleaners can damage the finish.



#### CANADA OFFICE

2995 Page Street, London  
 Ontario, Canada, N5V 4P6  
 Ph: 1-800-265-9055 / 519-453-5910  
 Fax: 519-455-0037  
 Email: sales@gss.ca  
 www.generalstoragesystems.com

#### U.S.A. OFFICE

P.O. Box #583  
 O'Fallon, MO 63366  
 Ph: 314-517-6975  
 Fax: 636-379-0088  
 Email: sales@generalstoragesystems.com